

MCCTV1

Wireless Mobile CCTV System




Main Features



Standard HD
Resolution forklift
camera



Wireless forklift
camera & display
monitor




7" Inch Display
Monitor



IP69K - Camera



High Temperature
Resistance



Shock-proof forklift
camera

Specifications

Camera	
Resolution	720P
Sensor	1/3" Color CMOS
Effective Pixels	1280x960
Minimum Illumination	0.1 Lux
Horizontal Angle of View	45°
Body Material	Stainless Steel
Ingress Protection	IP69K
Shockproof Rating	10G
Operating Voltage	12 VDC
Dimension	127 x 37 x 24.5 mm
Standard Accessory for Camera	Power Bank
Batteries Type	Lithium ion battery
Battery Capacity	10000 mAH
USB Input (Support fast charging)	5V (3.5A) / 9V (2A) / 12V (1.5A)
Power Bank Power Output	12VDC (0.8A)
Power Bank Ingress Protection	IP66
Power Bank Shockproof Rating	6G
Monitor Display	
Display	7" Color TFT-LCD
Operation Frequency	2400 ~ 2483.5MHz
Receiving Sensitivity	≤-86dBm(1MHZ QPSK MD300RE)
Resolution	1024×(RGB)×600
View Angle	(LR/UD) L/R: 60/70 U/D: 60/70
Contrast Ratio	500:1
Luminance(cd/m ²)	600
Response Time (ms)	25
Line of Sight Range	≤100M
Body Material	ABS
Load Dump	DC 12+87V/400ms
Operating Temperature	-20°C ~ +60°C
Storage Temperature	-30°C ~+80°C
Operating Voltage	8 ~ 32 VDC
Power Consumption	Max 5W
Dimension	185 x 122 x 28 mm