

MCCTV2

Wireless Mobile CCTV System




Main Features



Night vision distance
approximately 15m



Wireless connection
camera & display
monitor



7" Inch Display
Monitor



IP69K - Camera



High Temperature
Resistance



Up to 4 channels
(Support Quad-view)

Specifications

Camera	
Resolution	1.0MP
Sensor	1/3.7" Color CMOS
Effective Pixels	1280x720
Minimum Illumination	0.1 Lux, 0 Lux (with IR)
Lens Angle	120°
Lens	F = 2.8mm
Body Material	Stainless Steel
Ingress Protection	IP69K
Current Consumption	Max. 400 mA/12V
Operating Voltage	12-32 VDC
Night vision distance	approx. 15 m
Decompression form	H.264
Operating Temperature	-20°C~60°C
Storage Temperature	-30°C ~+80°C
Transmitting distance	300m
Transmitting speed	12Mbps
Monitor Display	
Display	7" Color TFT-LCD
Operation Frequency	2412 - 2467 MHz
Receiving Sensitivity	-85 dBm
Resolution	1024×3(RGB)×600
View Angle	U: 80 / D: 85, R/L: 85
Contrast Ratio	800:01:00
Aspect Ratio	16:09
Channel	Up to 4 channels (Support Quad-view)
TF Card Max.	128G
System Format	PAL / NTSC
Load Dump	DC 12+87V/400ms
Operating Temperature	-20°C ~ +70°C
Storage Temperature	-30°C ~+80°C
Power Consumption	Max 8W
Transmitting distance	300m